

RSK Standard Steel Straight Edge



FEATURES

- Made of finely seasoned carbon tool steel and ground finish .
- This rule is used as a standard for the precise inspection of flatness, straightness, etc. of various workpieces and for the precise marking-off.
- A-Class Hardened to HS65 or more.
- Not hardened.

SPECIFICATIONS

Unit = mm

Code	Nominal Size	Length	Width	Thickness	Straightness	Net Weight (kg)
556-0500	500	500	50	10	0.007	2.0
556-0750	750	750	50	10	0.010	2.9
556-1000	1000	1000	60	12	0.012	5.7
556-1500	1500	1500	70	15	0.017	12.4
556-2000	2000	2000	80	18	0.022	22.6
556-2500	2500	2500	100	18	0.027	35.3
556-3000	3000	3000	120	22	0.032	62.2
556-0500Q	500	500	50	10	0.007	2.0
556-0750Q	750	750	50	10	0.010	2.9
556-1000Q	1000	1000	60	12	0.012	5.7
556-1500Q	1500	1500	70	15	0.017	12.4
556-2000Q	2000	2000	80	18	0.022	22.6
556-2500Q	2500	2500	100	18	0.027	35.3
556-3000Q	3000	3000	120	22	0.032	62.2

RSK Knife-Type Straight Edge



FEATURES

- Made of finely seasoned carbon tool steel and ground finish.
- These straight edges are used for testing flat surfaces, where great accuracy is required.

SPECIFICATIONS

Unit = mm

Code	Nominal Size	Length	Width	Straightness	Net Weight (kg)
552-080	80	80	23	0.0013	0.14
552-100	100	100	24	0.0014	0.16
552-125	125	125	25	0.0015	0.19
552-150	150	150	25	0.0016	0.24
552-200	200	200	30	0.0018	0.40
552-250	250	250	30	0.0020	0.45
552-300	300	300	32	0.0022	0.65
552-400	400	400	35	0.0026	0.90
552-500	500	500	40	0.0034	1.50