


## **KOMBI GRIP**

Innovative two way clutch and needle roller clamping system ensures secure clamping at the tool flange periphery. Safe design eliminates any possibility of damage to the shank taper during the tightening process.



Catalog Number	HSK (Form A/E/F)	BIG CAPTO	ØC	ØD	Н	ØР	ØM
KG25R	25	_	1.890	3.110	2.559	2.441	.276 (For M6) or UNC 1/4
KG32R	32	C3	2.165	3.346		2.717	
KG40R	40	C4	2.480	3.661	2.756	3.031	
KG50R	50	C5	2.953	4.134		3.504	
KG63R	63	C6	3.465	4.862	2.953	4.154	.354 (For M8) or UNC 5/16
KG80R	80	C8	4.213	5.591	3.543	4.882	
KG100R	100	_	5.000	6.378	3.937	5.669	

- Mounting bolts (4 pcs.) must be ordered separately
  KOMBI GRIP can be used for BIG CAPTO; polygon taper made by other manufacturers cannot be used



KOMBI GRIP must be securely fixed to a bench with 4 mounting bolts.

## ST LOCK

Ideal fixture for the setup of cylindrical shank tool holders. Clamps Ø20, 25 & 32mm shanks by replacing the sleeve.



- 1 pc. each of Ø20mm, 25mm and 32mm sleeves are included
- Mounting bolts (4 pcs.) must be ordered separately



ST LOCK must be securely fixed to a bench with 4 mounting bolts.