

RSK Precision Square Level



SPECIFICATIONS

Unit = mm

Code	Size	Sensitivity (Per 1m)	Parallelness and Squareness	Net Weight (kg)
541-1002	100	0.02mm/4sec	0.01	1.0
541-1005	100	0.05mm/10sec	0.01	1.0
541-1001	100	0.1mm/20sec	0.01	1.0
541-1502	150	0.02mm/4sec	0.01	2.1
541-1505	150	0.05mm/10sec	0.01	2.1
541-1501	150	0.1mm/20sec	0.01	2.1
541-2002	200	0.02mm/4sec	0.01	3.8
541-2005	200	0.05mm/10sec	0.01	3.8
541-2001	200	0.1mm/20sec	0.01	3.8
541-2502	250	0.02mm/4sec	0.01	5.8
541-2505	250	0.05mm/10sec	0.01	5.8
541-2501	250	0.1mm/20sec	0.01	5.8
541-3002	300	0.02mm/4sec	0.01	7.5
541-3005	300	0.05mm/10sec	0.01	7.5
541-3001	300	0.1mm/20sec	0.01	7.5

FEATURES

- Made of high quality cast iron, measuring surfaces are lapped finish.
- All levels are packed in wooden cases.

RSK Precision Flat Level



FEATURES

- Made of high quality cast iron, measuring surfaces are lapped finish.
- All levels are packed in wooden cases.

SPECIFICATIONS

Unit = mm

Code	Size	Sensitivity (Per 1m)	V-Groove: Flat Face	Net Weight (kg)
542-1502	150	0.02mm/4sec	0.01	1.3
542-1505	150	0.05mm/10sec	0.01	1.3
542-1501	150	0.1mm/20sec	0.01	1.3
542-2002	200	0.02mm/4sec	0.01	1.7
542-2005	200	0.05mm/10sec	0.01	1.7
542-2001	200	0.1mm/20sec	0.01	1.7
542-2502	250	0.02mm/4sec	0.01	2.3
542-2505	250	0.05mm/10sec	0.01	2.3
542-2501	250	0.1mm/20sec	0.01	2.3
542-3002	300	0.02mm/4sec	0.01	2.8
542-3005	300	0.05mm/10sec	0.01	2.8
542-3001	300	0.1mm/20sec	0.01	2.8
542-4502	450	0.02mm/4sec	0.01	4.5
542-4505	450	0.05mm/10sec	0.01	4.5
542-4501	450	0.1mm/20sec	0.01	4.5
542-6002	600	0.02mm/4sec	0.01	6.0
542-6005	600	0.05mm/10sec	0.01	6.0
542-6001	600	0.1mm/20sec	0.01	6.0